Novonanmek

The Three-Part Corridor Archetype: Cross-Domain Architectural Standardization in HOPT-AS and HLAS Clean Energy Infrastructure

Abstract

Traditional macro-regional energy infrastructure is heavily exposed to asset stranding, cross-chain counterparty default, and single-point-of-failure (SPOF) risks due to rigid, linear design patterns. This paper introduces the **Three-Part Corridor Archetype** as a universal, low-risk infrastructure baseline that standardizes regional network geometry. By cross-referencing two independent frameworks pioneered by Novonanmek Material Sciences—the **Hub-Only Pipeline Topology Architecture Standard (HOPT-AS)** and the **Hydrogen Logistics Architecture Standard (HLAS)**—we demonstrate that both standards utilize an identical, three-part spatial corridor consisting of **End 1**, **End 2**, and an **Intermediate Length**.

We define this 3-region length as the universal **Standardized Spatial Element (SSE)**. This paper outlines how the SSE simplifies network expansion: in HLAS, the initial endpoints of multiple elements connect seamlessly via backbone pipelines, while in HOPT-AS, these elements chain together to form macro-regional and national networks. This structural standardization establishes a highly scalable, minimum-risk baseline for institutional project finance in clean energy infrastructure.

1. The Core Paradigm: Standardizing the Corridor, Not the Project

In conventional infrastructure planning, networks are built as bespoke, project-specific delivery lines. If an input plant slows production or a downstream consumption facility closes, the unyielding physical line becomes a multi-million-dollar stranded asset. To solve this, a fundamental architectural shift is required: **we must standardize the physical structure of the transmission corridor itself, rather than the assets attached to it.**

By treating the infrastructure grid as a repeatable, **Standardized Spatial Element (SSE)** bounded by two anchoring ends and a shared intermediate length, the network transitions from a fragile delivery straw into a resilient balancing bridge. This universal archetype is deployed natively across two distinct frameworks: HOPT-AS for carbon management and HLAS for hydrogen distribution.

2. Structural Configuration: Who Occupies What?

The power of this cross-domain standardization is that the **three-part geometry remains invariant**, even though the industrial operators occupying the nodes change completely between the two standards.

© 2026 Novonanmek Material Sciences Private Limited

info@novonanmek.com




Figure 1: Novonanmek Universal Three-Part Corridor Blueprint.

2.1 The HOPT-AS Corridor Layout (Carbon Balancing)

In carbon capture management, the three-part corridor is optimized to shield the pipeline from volatile private-industrial boundaries:

- **End 1 (Hub A):** Occupied by a centralized carbon collection and regeneration hub. Localized carbon emitters are decoupled from the grid, connecting to this hub exclusively via flexible solid material logistics (e.g., trucks/rail carrying mineralized carbon products).
- **End 2 (Hub B):** Occupied by a corresponding mirrored carbon hub on the opposite end of the regional network, similarly fed by decoupled emitters via solid logistics.
- **The Intermediate Length (The Storage/Utilization Zone):** Occupied strictly by a high-capacity pipeline bridge tapped by single or multiple **Storage/Utilization (S/U) sites**.




Figure 2

© 2026 Novonanmek Material Sciences Private Limited `

2.2 The HLAS Corridor Layout (Hydrogen Distribution)

In regional hydrogen network planning, the three-part corridor is governed by **Section 6 (Architecture Rules)** to optimize bulk molecule routing:

- **End 1 (Production Hub):** Occupied by a primary certified **Hydrogen Production Hub** where clean hydrogen is generated at scale.
- **End 2 (Terminal Aggregation Node / Exit Gate):** Occupied by a **Regional Aggregation Hub or Export Hub**, which handles bulk distribution, off-take routing, or international transport gates at the perimeter of the network.
- **The Intermediate Length (The Backbone Corridor):** Occupied strictly by a high-pressure Pipeline that connects the production source directly to the exit gate. Large industrial users, consumer demand centers, and cavernous geological storage facilities tap directly into the mid-length of this pipeline bridge.




Figure 3

3. Direct Topological Comparison

The architectural symmetry between the two standards can be directly scanned and compared using the structural matrix below:

Corridor Segment	**Universal Geometric Function**	**HOPT-AS Occupant (Carbon Vector)**	**HLAS Occupant (Hydrogen Vector)**
End 1	Initial Aggregation / Boundary Node	**Regeneration Hub A** (Fed via solid material logistics)	**Hydrogen Production Hub** (Bulk generation source)
Intermediate Length	Central Transmissive Bridge / Tapping Zone	**Gaseous Pipeline** tapped by single or multiple **Storage/Utilization (S/U) sites**	**Backbone Pipeline Corridor** tapped by **Large Industrial Users & Cavity Storage**

© 2026 Novonanmek Material Sciences Private Limited

info@novonanmek.com

End 2	Terminal Aggregation / Balancing Node	**Regeneration Hub B** (Fed via solid material logistics)	**Regional Aggregation Hub / Export Gate**

4. Multi-Phase Scaling and Network Expansion

Because the three-part corridor is treated as a self-contained **Standardized Spatial Element (SSE)**, scaling a regional network no longer requires rebuilding existing transmission systems. Instead, macro-regional and national expansion becomes a plug-and-play engineering exercise, though the scaling mechanics adapt naturally to each energy vector:

4.1 HLAS Scaling Behaviour: End-to-End Interconnection

In the **HLAS** framework, macro-regional growth is achieved by daisy-chaining the endpoints of independent elements. The **End 1 (Production Hub)** of multiple scattered SSE blocks can be directly interconnected via centralized **Backbone Pipelines**. This creates an interconnected super-grid of supply nodes that can dynamically pool hydrogen volumes and route them across multiple Intermediate Length corridors to distant export gates or heavy industrial clusters seamlessly.

4.2 HOPT-AS Scaling Behaviour: Modular Element Chaining

In the **HOPT-AS** framework, scaling is achieved by physically chaining full elements together to build out an expansive national network. Because each SSE contains built-in bi-directional balancing, a new industrial cluster can be on-boarded simply by attaching a new SSE onto the existing hub nodes. For example, **Hub B (End 2)** of the initial corridor can simultaneously act as **Hub A (End 1)** for the next corridor. This modular concatenation allows a network to grow organically from a single localized valley into a massive, multi-hub national grid infrastructure without increasing the risk profile for investors.

5. Conclusion

The true breakthrough of Novonanmek's dual-standard framework is the verification that **the three-part corridor is a universal law of low-risk infrastructure design.** Whether managing carbon capture networks via HOPT-AS or high-pressure transmission networks via HLAS, the geometric formula remains identical. By formalizing this structure as a repeatable **Standardized Spatial Element (SSE)**, scaling constraints are completely removed. The archetype allows independent pipelines to easily link up in HLAS or chain together into a national network in HOPT-AS, providing public authorities and institutional sponsors with a highly predictable, modular, and bankable macro-regional network blueprint.

© 2026 Novonanmek Material Sciences Private Limited info@novonanmek.com

References

1. Sinha, A. (2026). *The Triadic Law of Systems Reliability: Preventing Failure, Securing Lifecycle Continuity, and De-Risking Capital Allocation via the Three-Point Architecture Benchmark*. Novonanmek Material Sciences Private Limited. https://novonanmek.com/
2. Sinha, A. (2026). *The Triadic Law of Infrastructure Resilience: De-Risking Capital Allocation via the Three-Point Architecture Principle*. Novonanmek Material Sciences Private Limited. https://novonanmek.com/
3. Sinha, Arnab, *Hub Only Pipeline Topology Architecture Standard Version v1.31 (HOPT-AS v1.31)* (April 04, 2026). Available at SSRN: https://ssrn.com/abstract=6143086 or http://dx.doi.org/10.2139/ssrn.6143086
4. Sinha, Arnab, *Hydrogen Logistics Architecture Standard Version 1.11 (HLASv1.11): A Deterministic Architecture for Bankable Hydrogen Infrastructure* (December 01, 2025). Available at SSRN: https://ssrn.com/abstract=6667160 or http://dx.doi.org/10.2139/ssrn.6667160
5. Sinha, A. (2026). *Nuclear Repowering Interface Architecture (NRIA): Standardization of Nuclear Repowering—A Three-Point Framework for Classifying Turbines, Heat Output and Interface Architectures*. Novonanmek Material Sciences Private Limited. https://novonanmek.com/
6. Sinha, A. (2026). *Nuclear Engineering Interface Architecture (NEIA): Standardization of SMR Integration.* Novonanmek Material Sciences Private Limited. https://novonanmek.com/

How to cite this paper:

Sinha, A. (2026). *The Three-Part Corridor Archetype: Cross-Domain Architectural Standardization in HOPT-AS and HLAS Clean Energy Infrastructure*. Novonanmek Material Sciences Private Limited. https://novonanmek.com/

© 2026 Novonanmek Material Sciences Private Limited info@novonanmek.com